

Multi-Hazard Suppression Systems



AH-03233

QSP-32



QSP-120 1 cross-zone



QSP-120 5 cross-zone

AH-03233 Releasing Indicator

- The display can be set according to customer's requirements.

QSP-32 Manual Pull Station

- Emergency Start/Stop switch, Auto/Manual key switch.
- Power LED, Releasing LED, Start LED, Stop LED, Auto LED, and Manual LED.
- Digital release countdown.

QSP-120 Multi-Hazard Suppression Control Panel

- Panel and manual pull station count-down simultaneously.
- Discharge delay timer setting (20~999 seconds).
- Cross-zone detection confirmation makes better stability.
- Built-in phone jacks on both panel and manual pull station.
- Expandable to 5 cross-zone detection sections.
- Each section has manual/auto operation mode.
- Wiring trouble inspection.
- Through dipswitch to select the supervision on feed-back signal of agent discharge.
- All 24V output contacts are protected by fuse.

Specifications

Model	AH-03233
Supply Voltage	24V DC 670mA (bulb) 310mA (LED)
Light Source	1W bulb x 18 or ø5 LED RED x 28
Display Type	Non-flash
Material	0.8mm stainless steel
Color	Red
Dimensions	155mm(H) x 405mm(W) x 60mm(D)



Specifications

Model	QSP-32
Supply Voltage	24V DC
Material	1.2mm stainless steel
Color	Red
Dimensions	160mm(H) x 165mm(W) x 50mm(D)



Specifications

Model	QSP-120
Power	220VAC 50/60Hz * others also available
Battery Capacity	1 cross-zone: 24VDC 1.2Ah 5 cross-zone: 24VDC 4Ah
Zone voltage	24VDC
EOL Resistor	4.7kΩ
Detection Type	Cross-zone detection
# of heat detectors connected	No limit *Except electronic-type
# of smoke detectors connected	25/zone *Horing Lih manufactured
Dimensions(mm)	1 cross-zone : 350 (H) x 400 (W) x 130 (D) 5 cross-zone : 550 (H) x 400 (W) x 130 (D)
Color	Ivory

