



Vivid 32

Fire Alarm Control Panel

Characteristics

- Model range from 1 to 32 zones.
- AC power supply has passed EMI (Electromagnetic Interference).
- Each zone has a separate disable function.
- Double sets of sounder outputs.
- Long-term or temporary silencing feature.
- Microprocessor-base design.
- Zonal sounder circuit with supervision.
- LCD (24x2 lines) for events display and store capacity up to 255 events.
- Fire Relay Output contacts and Fault Relay Output contacts.
- Switch membrane provides longer service and is water-proof, dust resistant and easy to clean.

Specifications

Model	Vivid 32	
Power	220V AC, 50/60Hz *Others also available	
Battery Capacity	1~16 zone 24V/4 Ah	17~32 zone 24V/7Ah
Max. Output Current	2A @24V DC	
# of heat detectors connected	No limit *Except electronic-type	
# of smoke detectors connected	30/zone *Horing Lih manufactured	
Max. No. of Bells @25mA	40 per sounder circuit	
End of Line Resistor	4.7kΩ *One per zone	
Material	1.2mm steel plate	
Dimensions (H x W x D) mm	350 x 350 x 100 400 x 350 x 125 (with zone indication)	
Optional Features	Individual zone indication	



EN54 
pending